

LED 摄影棒灯

用户手册 V1.0



感谢您选择我们的产品。请仔细阅读说明书并按手册使用。


产品特性

- 1.使用高显指LED灯组合,发热量小,使用寿命长。
- 2.亮度及色温可调节。
- 3.内置锂电池,可以重复充放电。
- 4.采用专业的LED驱动芯片,光线稳定,效率高达93%。
- 5.高亮度,最大1000流明,适用于需要补充光线的情况。
- 6.可调节全色色0-360°色调及颜色饱和度
- 7.21个预设环境效果
- 8.两洲1/4安装螺孔,可搭配三脚架及其它设备使用
- 9.应用:摄影照明、应急照明等。

配置

LED灯棒 : 1只
充电器 : 1只
USB线 : 1条
说明书 : 1本


部件名称



安装摄影灯

- 1.通过1/4固定螺丝与补光灯底部螺母对准推入,旋转拧紧为止。
- 2.旋转角度调节旋钮来改变补光灯的角度,使灯光调至合适位置。

按键操控使用方法



- 1. 预计剩余使用时间
- 2. 模式显示
- 3. 电池电量
- 4. 选择三角标
- 5. 色温显示
- 6. 亮度显示
- 7. 色彩饱和度
- 8. 色温显示
- 9. 预设环境效果组别
- 10. 预设环境效果名称

- 1.长按功能键2秒开机,长按功能键2秒关机。
- 2.开机状态下单击模式键可选择CCT/HSI/EFFECT三种模式
- 3.CCT模式:短按选择键可选择调节色温亮度,显示屏上▶为当前调节参数,+-按键增加或减少该参数。
- 4.HSI模式:短按选择键可选择调节色温、饱和度和亮度,显示屏上▶为当前调节参数,+-按键增加或减少该参数。色温调节范围为0~360°,色彩饱和度调节范围为0~100。
- 5.光亮度时,显示屏会显示当前电量和充满所需的时间。
- 6.使用时,显示屏会显示当前电量和可持续使用时间,当显示的电量电量已空时需要立即充电。
- 7.单击模式键转换赋予EFFECT模式,在EFFECT模式档位下短按选择键会循环切换21种预设环境效果

预设环境效果名单

- A:闪光/快闪/电视屏幕光
- B:蜡烛/火焰1/火焰2
- C:警车/救护车/消防车
- D:频闪1/频闪2/频闪3
- E:慢速渐变/中速渐变/快速渐变
- F:烟花1/烟花2/烟花3
- G:俱乐部1/俱乐部2/浪漫

规格

功率	10W
电池	3.7V 5200mAh
光照角度	120°
色温	2500-9900K
显色指数	RA>95
光亮度	1000LM
尺寸	326*37*35mm
重量	310g
使用温度	0-40°C

注:此灯具光源是不可替换,当光源到其寿命时,应替换整个灯具。

注意事项

- 1.请勿将本产品在高温或极端环境中放置或者使用,请勿放在阳光下暴晒。
- 2.避免将摄影光放置在酒精、汽油、易燃或挥发性溶剂附近,这些溶剂会引起火灾或损坏摄影光。
- 3.不要让设备暴露在水或其他液体中,造成短路和损坏产品。
- 4.请勿擅自拆卸本产品,请勿大力震动、敲打、撞击本产品。
- 6.儿童请在监护人员的陪同下使用该产品,避免直射、伤害眼睛。
- 7.请至少3个月为本产品充满电一次。
- 8.摄影灯点亮时请不要盯着灯珠,避免灯光直射,伤害眼睛。
- 9.正常工作均有可能产品温度升高,使用期间或使用完毕后,请小心取拿,避免烫伤。
- 11.产品开灯是发光功率较大,请勿将发光面覆盖,以避免造成补光灯损坏或意外事故发生。

产品充电及续航时间

续航时间:2-32小时(最高档-最低档)
充电时间:3-4小时(5V/2A适配器)



内含电池
请勿随意丢弃产品

保修卡

用户信息
用户名称: _____ 联系电话: _____

联系地址: _____

产品信息

产品型号: _____ 销售日期: _____

产品维修记录送检时间

送修时间	维修中心名称	故障及处理情况	完成日期

经销商信息

单位名称: _____ 销售日期: _____

联系地址: _____

LED Video Light Wand

User Manual V1.0

■ Features

[Excellent Lighting Configuration]

Using 100 high-quality non-flashing LEDs (72pcs white LEDs, 28pcs warm LEDs, 36pcs RGB LEDs) with max power 10W, 2500K-9900K color temperature, CRI>95

[Precision Circuit Control]

With built-in professional LED driver chip and accurate dimming circuit, there is no ripple or strobe phenomenon when shooting which perfectly matches with high-lumen SMD LEDs to reach more accurate brightness. High color rendering index, soft and uniform light, especially suitable for live broadcast, selfie, still life shooting, short video recording, camping and so on.

[Three Usage Modes, Colors can be Adjusted as You like]

With CCT cold and warm mode, the adjustable range of color temperature is 2500K-9900K. HSI color mode has 36,000 finely adjustable colors. HUE is adjustable from 0-360°, and SAT saturation is adjustable from 1-100. What's more surprising is that the EFFECT mode presets 21 scenarios. All three modes can be matched with 1-100 brightness adjustment.

[21 Dynamic Effects in EFFECT Mode]

7 large groups of different scene simulations, each group contains 3 effects, which can be combined as you like and the brightness is adjustable. Help take photos or photography to render different atmospheres and meet the needs of the storyline.

[Built-in High-Capacity & Rechargeable 5200mAh Battery]

Rest assured to use it in outdoor or indoor. Using Class A lithium battery, and it also supports pass-through charging with USB-C 5V/2A input.


[Fashionable Appearance With Aluminum Alloy Shell]

The whole shell adopts aluminum alloy oxidation process with OLED display which is of strong texture anti-compression and anti-rattle. Better heat dissipation. The body has two 1/4 inch universal screw holes. The small size can fit directly into your camera bag.

■ Caution

- Use original or certified cables.
- Do not disassemble or repair it by yourself.
- Avoid lightning strikes, knocking and dropping.
- Please charge fully every 4 months to extend the battery life.
- Avoid extreme temperatures.
- Do not expose to water or chemicals.


■ Product Interface



■ Specification

Power: 10W(Max)
Color Temperature Range: 2500K-9900K (±2500K)
RGB Hue (HSI): 0-360° Full Color Adjustable
Color Saturation Adjustment: 1-100
Brightness Adjustment: 1-100%
Luminous Flux: 1200LM (0.5m 5600)
Color Rendering Index (CRI): Ra>95
Mode: CCT/HSI/Effect Mode
Effect Mode Scene: 21 Scenes Supportable
Built-in Battery: 5200mAh Lithium Battery
Input: USB-C 5V/2A
Fixed Interface: 2*1/4 inch Screw Hole
Shell Material: Aluminium Alloy
Dimensions: 324*37*38mm
Weight (Approx): 310g

■ Display Interface



- 1. Estimated Remaining Usage Time
- 2. Current Mode (CCT/HSI/EFFECT)
- 3. Battery Level
- 4. Current adjustment items
- 5. Color Temperature (CCT Mode)
- 6. Brightness (CCT Mode)
- 7. Color Saturation (S (HSI Mode))
- 8. Hue (H (HSI Mode))
- 9. Preset Scene Effect Group (EFFECT Mode)
- 10. Preset Scene Effect Name (EFFECT Mode)

■ Usage

1. On/Off
Long press the Power Button, then the video light turns on/off. When charging and discharging, it will turn on and off automatically, noneed to press the button.

2. Mode Switch

Press Power Button to select different modes (CCT/HSI/EFFECT)

3. CCT Mode

Press the button to select the color temperature and brightness.

1. Press "+" or "-" key to adjust the brightness (1%-100%)
2. Press "+" or "-" key to adjust the color temperature (2500K-9900K)



4. HSI Mode

Press the button to select H (hue), S (saturation), brightness.

1. Press "+" or "-" key to adjust H (tone) (0-360°)
2. Press "+" or "-" key to adjust S (saturation) (0-100)
3. Press "+" or "-" key to adjust (brightness) (1%-100%)



5. EFFECT Mode

Press the button to select the scene effect group and scene effect name.

Turn the Brightness Adjustment Dial to adjust the needed brightness (1% to 100%)



■ 21 Dynamic Sence Effect

- Group A: Flash/Flash Fast/TV screen
- Group B: Candle/Flame 1/Flame 2
- Group C: Police/Ambulance/Fire truck
- Group D: Strobe Lights 1/Strobe Lights 2/Strobe Lights
- Group E: Chase slow/Chase mid/Chase fast
- Group F: Fire work 1/Fire work 2/Fire work 3
- Group G: Club 1/Club 2/Romantic

■ How to Charge

Equipped with a 5V USB-C input, please correctly connect the charging cable to the power supply unit. The OLED display will show the charging status when charging. The maximum charging current of this product is 5V/2A, so the recharging time depends on the charging adapter you used.

■ How to Install the Cole Shoe

1. Align the screw of the cold shoe adapter with the 1/4 inch screw hole of this product
2. Turn the locking ring clockwise to fix the cold shoe adapter on the product.

■ How to Install the Camera

1. Turn off the light.
2. Slide the bottom of the adapter of the product with the adapter installed into the camera hot shoe or cold shoe mount

■ How to Remove the Camera

1. Turn off the RGB-B320.
2. Turn the locking ring clockwise and remove the adapter from the camera/cold shoe mount.

■ What's in the box?

- 1. SP-320C RGB LED Video Light
- 2. USB-C cable
- 3. User Manual

■ Warning

Inappropriate use may cause product damage or pose potential physical injury and potential physical injury and property loss.

■ Safety Warning

Please do not use LED to illuminate human eyes at close range, otherwise it may temporarily affect your eyesight. We highly recommend you use it in a way or consider using a diffuser. Please do not place this product near alcohol or flammable materials.

This product is not waterproof or dust-proof, please do not place this product near liquids.

Please use a soft cloth and neutral detergent to clean it. Please do not use alcohol or corrosive solvents to clean it. Please store and use it below 40 degrees, and pay more attention when you use it outdoors for a long time under sunlight. please do not use this product outdoors for a long time to avoid overheating and possible damage.

With a built-in lithium battery, please do not disassemble, hit or burn this product by yourself.

Please use certified charging cable and adapter to recharge it to avoid accidents.

Please fully recharge it once a month to extend the battery life.

If you do not use this product for a long time, please be sure to charge it before using it again.

The performance of the lithium battery will gradually decrease with the use of this product, so as the using time.

When the LED is used at the same time during charging, to avoid overheating, the product may not work normally or automatically shut down due to overheating.

LED Video Light Wand

User Manual V1.0

■ Features

[Excellent Lighting Configuration]

Using 100 high-quality non-flashing LEDs (72pcs white LEDs, 28pcs warm LEDs, 36pcs RGB LEDs) with max power 10W, 2500K-9900K color temperature, CRI>95

[Precision Circuit Control]

With built-in professional LED driver chip and accurate dimming circuit, there is no ripple or strobe phenomenon when shooting which perfectly matches with high-lumen SMD LEDs to reach more accurate brightness. High color rendering index, soft and uniform light, especially suitable for live broadcast, selfie, still life shooting, short video recording, camping and so on.

[Three Usage Modes, Colors can be Adjusted as You like]

With CCT cold and warm mode, the adjustable range of color temperature is 2500K-9900K. HSI color mode has 36,000 finely adjustable colors. HUE is adjustable from 0-360°, and SAT saturation is adjustable from 1-100. What's more surprising is that the EFFECT mode presets 21 scenarios. All three modes can be matched with 1-100 brightness adjustment.

[21 Dynamic Effects in EFFECT Mode]

7 large groups of different scene simulations, each group contains 3 effects, which can be combined as you like and the brightness is adjustable. Help take photos or photography to render different atmospheres and meet the needs of the storyline.

[Built-in High-Capacity & Rechargeable 5200mAh Battery]

Rest assured to use it in outdoor or indoor. Using Class A lithium battery, and it also supports pass-through charging with USB-C 5V/2A input.


[Fashionable Appearance With Aluminum Alloy Shell]

The whole shell adopts aluminum alloy oxidation process with OLED display which is of strong texture anti-compression and anti-rattle. Better heat dissipation. The body has two 1/4 inch universal screw holes. The small size can fit directly into your camera bag.

■ Caution

- Use original or certified cables.
- Do not disassemble or repair it by yourself.
- Avoid lightning strikes, knocking and dropping.
- Please charge fully every 4 months to extend the battery life.
- Avoid extreme temperatures.
- Do not expose to water or chemicals.


■ Product Interface



■ Specification

Power: 10W(Max)
Color Temperature Range: 2500K-9900K (±2500K)
RGB Hue (HSI): 0-360° Full Color Adjustable
Color Saturation Adjustment: 1-100
Brightness Adjustment: 1-100%
Luminous Flux: 1200LM (0.5m 5600)
Color Rendering Index (CRI): Ra>95
Mode: CCT/HSI/Effect Mode
Effect Mode Scene: 21 Scenes Supportable
Built-in Battery: 5200mAh Lithium Battery
Input: USB-C 5V/2A
Fixed Interface: 2*1/4 inch Screw Hole
Shell Material: Aluminium Alloy
Dimensions: 324*37*38mm
Weight (Approx): 310g

■ Display Interface



- 1. Estimated Remaining Usage Time
- 2. Current Mode (CCT/HSI/EFFECT)
- 3. Battery Level
- 4. Current adjustment items
- 5. Color Temperature (CCT Mode)
- 6. Brightness (CCT Mode)
- 7. Color Saturation: S (HSI Mode)
- 8. Hue: H (HSI Mode)
- 9. Preset Scene Effect Group (EFFECT Mode)
- 10. Preset Scene Effect Name (EFFECT Mode)

■ Usage

1. On/Off
Long press the Power Button, then the video light turns on/off. When charging and discharging, it will turn on and off automatically, noneed to press the button.

2. Mode Switch

Press Power Button to select different modes (CCT/HSI/EFFECT)

3. CCT Mode

Press the button to select the color temperature and brightness.

1. Press "+" or "-" key to adjust the brightness (1%-100%)
2. Press "+" or "-" key to adjust the color temperature (2500K-9900K)



4. HSI Mode

Press the button to select H (hue), S (saturation), brightness.

1. Press "+" or "-" key to adjust H (tone) (0-360°)
2. Press "+" or "-" key to adjust S (saturation) (0-100)
3. Press "+" or "-" key to adjust (brightness) (1%-100%)



5. EFFECT Mode

Press the button to select the scene effect group and scene effect name.

Turn the Brightness Adjustment Dial to adjust the needed brightness (1% to 100%)



■ 21 Dynamic Sence Effect

- Group A: Flash/Flash Fast/TV screen
- Group B: Candle/Flame 1/Flame 2
- Group C: Police/Ambulance/Fire truck
- Group D: Strobe Lights 1/Strobe Lights 2/Strobe Lights
- Group E: Chase slow/Chase mid/Chase fast
- Group F: Fire work 1/Fire work 2/Fire work 3
- Group G: Club 1/Club 2/Romantic

■ How to Charge

Equipped with a 5V USB-C input, please correctly connect the charging cable to the power supply unit. The OLED display will show the charging status when charging. The maximum charging current of this product is 5V/2A, so the recharging time depends on the charging adapter you used.

■ How to Install the Cole Shoe

1. Align the screw of the cold shoe adapter with the 1/4 inch screw hole of this product
2. Turn the locking ring clockwise to fix the cold shoe adapter on the product.

■ How to Install the Camera

1. Turn off the light.
2. Slide the bottom of the adapter of the product with the adapter installed into the camera hot shoe or cold shoe mount

■ How to Remove the Camera

1. Turn off the RGB-B320.
2. Turn the locking ring clockwise and remove the adapter from the camera/cold shoe mount.

■ What's in the box?

- 1. SP-320C RGB LED Video Light
- 2. USB-C cable
- 3. User Manual

■ Warning

Inappropriate use may cause product damage or pose potential physical injury and potential physical injury and property loss.

■ Safety Warning

Please do not use LED to illuminate human eyes at close range, otherwise it may temporarily affect your eyesight. We highly recommend you use it in a way or consider using a diffuser. Please do not place this product near alcohol or flammable materials.

This product is not waterproof or dust-proof, please do not place this product near liquids.

Please use a soft cloth and neutral detergent to clean it. Please do not use alcohol or corrosive solvents to clean it. Please store and use it below 40 degrees, and pay more attention when you use it outdoors for a long time under sunlight. please do not use this product outdoors for a long time to avoid overheating and possible damage.

With a built-in lithium battery, please do not disassemble, hit or burn this product by yourself.

Please use certified charging cable and adapter to recharge it to avoid accidents.

Please fully recharge it once a month to extend the battery life.

If you do not use this product for a long time, please be sure to charge it before using it again.

The performance of the lithium battery will gradually decrease with the use of this product, so as the using time.

When the LED is used at the same time during charging, to avoid overheating, the product may not work normally or automatically shut down due to overheating.

LED Video Light Wand

User Manual V1.0

■ Features

[Excellent Lighting Configuration]

Using 100 high-quality non-flashing LEDs (72pcs white LEDs, 28pcs warm LEDs, 36pcs RGB LEDs) with max power 10W, 2500K-9900K color temperature, CRI>95

[Precision Circuit Control]

With built-in professional LED driver chip and accurate dimming circuit, there is no ripple or strobe phenomenon when shooting which perfectly matches with high-lumen SMD LEDs to reach more accurate brightness. High color rendering index, soft and uniform light, especially suitable for live broadcast, selfie, still life shooting, short video recording, camping and so on.

[Three Usage Modes, Colors can be Adjusted as You like]

With CCT cold and warm mode, the adjustable range of color temperature is 2500K-9900K. HSI color mode has 36,000 finely adjustable colors. HUE is adjustable from 0-360°, and SAT saturation is adjustable from 1-100. What's more surprising is that the EFFECT mode presets 21 scenarios. All three modes can be matched with 1-100 brightness adjustment.

[21 Dynamic Effects in EFFECT Mode]

7 large groups of different scene simulations, each group contains 3 effects, which can be combined as you like and the brightness is adjustable. Help take photos or photography to render different atmospheres and meet the needs of the storyline.

[Built-in High-Capacity & Rechargeable 5200mAh Battery]

Rest assured to use it in outdoor or indoor. Using Class A lithium battery, and it also supports pass-through charging with USB-C 5V/2A input.

[Fashionable Appearance With Aluminum Alloy Shell]

The whole shell adopts aluminum alloy oxidation process with OLED display which is of strong texture anti-compression and anti-rattle. Better heat dissipation. The body has two 1/4 inch universal screw holes. The small size can fit directly into your camera bag.

■ Caution